



600A Clamp Multimeters

Amprobe's ACD-10 PLUS meters offer thinner jaws over standard clamp meters. Allowing access to tight measurement areas and still accomodating conductors up to 25 mm (1 in). Both meters also measure Capacitance and Frequency. Frequency is measured by either jaws or test leads. Very versatile clamp multimeters.

ACD-10 PLUS, ACD-10 TRMS-PLUS Clamp Multimeters with Unique Thin Jaws

- TRMS Measurement (ACD-10 TRMS PLUS only)
- AC and DC Voltage to 600V
- AC Current to 600A
- Resistance to 40 MΩ with Continuity Buzzer
- Capacitance to 3000 μF
- Frequency measurement
- Hold & Maximum reading functions
- Auto ranging
- Thinner jaws (approx 6.35mm thinner)
- In Rush Current
- Jaw opening 25 mm
- Safety acc. EN 61010, CAT III/600 V

FEATURES	ACD-10 TRMS-PLUS	ACD-10 PLUS
TRMS Measurement	Yes	N/A
AC Voltage	4,000, 40.00, 400.0, 600V	
DC Voltage	400.0m, 4,000, 40.00, 400.0, 600V	
AC Current	40.00, 400.0, 600A	
Resistance with Continuity Buzzer	0-400.0 Ω, 4,000 kΩ, 40.00 kΩ, 400.0 kΩ, 4,000 MΩ, 40.00 MΩ	
Capacitance	500.0nF, 5.000μF, 50.00μF, 500.0μF, 3000μF	
Frequency (Using Jaw or Test Leads)	40-400Hz with Jaw, 10Hz to 100kHz with test leads	