




1 2 3 4 5 6 7 8

DIMENSION:(UNIT:mm/inches)



Operation Temperature: -20°C to 70°C  
Storage Temperature: -40°C to 85°C

No.ofPOS	DIM.A	DIM.B
01	3.84(0.151)	—
02	6.08(0.239)	2.54(0.100)
03	8.92(0.351)	5.08(0.200)
04	11.16(0.439)	7.62(0.300)
05	13.70(0.539)	10.16(0.400)
06	16.24(0.639)	12.70(0.500)
07	19.08(0.751)	15.24(0.600)
08	21.32(0.839)	17.78(0.700)
09	24.16(0.951)	20.32(0.800)
10	26.40(1.039)	22.86(0.900)
12	31.48(1.239)	27.94(1.100)




C8300-XXSLXJX0R

C8300-XXSSXJX0R




P.C.B. LAYOUT



CONSTRUCTION

ITEM	DES	MATERIALS	TREATMENT
1	ACTUATOR	UL94V-0 PBT THERMOPLASTIC	WHITE
2	COVER	UL94V-0 PBT THERMOPLASTIC	BLUE, RED.BLACK
3	BASE	UL94V-0 PBT THERMOPLASTIC	BLACK
4	TERMINAL	PHOSPHOR BRONZE	GOLD PLATING
5	POTTING	EXPOXY	BLACK



CIRCUIT DIAGRAM

1 2 3 4 5 6 7 8